



10-25-00

PTO/SB/05 (08-00)

Approved for use through 10/31/2002. OMB 0651-0032

U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Please type a plus sign (+) inside this box →

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.



UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. YO998-100RA

First Inventor James D. Bennett

Title Combined Optical and Radio Frequency Tag Reader

Express Mail Label No. EK 834 920 035 US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)2. Applicant claims small entity status.
See 37 CFR 1.27.3. Specification [Total Pages 30]
(preferred arrangement set forth below)
- Descriptive title of the invention
- Cross Reference to Related Applications
- Statement Regarding Fed sponsored R & D
- Reference to sequence listing, a table,
or a computer program listing appendix
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure4. Drawing(s) (35 U.S.C. 113) [Total Sheets 11]

5. Oath or Declaration [Total Pages 3]

a. Newly executed (original or copy)
b. Copy from a prior application (37 CFR 1.63 (d))
(for continuation/divisional with Box 17 completed)
i. **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s)
named in the prior application, see 37 CFR
1.63(d)(2) and 1.33(b).

6. Application Data Sheet. See 37 CFR 1.76**ADDRESS TO:** Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

7. CD-ROM or CD-R in duplicate, large table or
Computer Program (Appendix)
8. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
a. Computer Readable Form (CRF)
b. Specification Sequence Listing on:
i. CD-ROM or CD-R (2 copies); or
ii. paper
c. Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

9. Assignment Papers (cover sheet & document(s))
10. 37 CFR 3.73(b) Statement Power of
(when there is an assignee) Attorney
11. English Translation Document (if applicable)
12. Information Disclosure
Statement (IDS)/PTO-1449 Copies of IDS
13. Preliminary Amendment
14. Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
15. Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. Other:

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment,
or in an Application Data Sheet under 37 CFR 1.76: Continuation Divisional Continuation-in-part (CIP)

of prior application No. 09, 247,460

Prior application information:

Examiner Jared Fureman

Group / Art Unit: 2876

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

18. CORRESPONDENCE ADDRESS

<input type="checkbox"/> Customer Number or Bar Code Label	(Insert Customer No. or Attach bar code label here)			<input type="checkbox"/> Correspondence address below	
				or	<input checked="" type="checkbox"/>
Name	John H. Sherman, Legal Department				
Address	Intermec Technologies Corporation				
	550 2nd Street, S.E.				
City	Cedar Rapids	State	Iowa	Zip Code	52401
Country	USA	Telephone	319-369-3661	Fax	319-369-3630

Name (Print/Type)	John H. Sherman	Registration No. (Attorney/Agent)	16,909
Signature			
	Date Oct. 23, 2000		

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Express Mail Label
No. EK 834 920 035 US

Attorney Docket
No. YO998-100RA

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

TITLE

COMBINED OPTICAL AND RADIO FREQUENCY TAG READER

INVENTOR

James D. Bennett
6712-A Hart Lane
Austin, TX 78731
Citizenship: USA


ASSIGNEE

INTERMEC IP CORP.
21900 Burbank Boulevard
Woodland Hills, California

CERTIFICATE OF EXPRESS MAILING

I hereby certify that this correspondence is being deposited with the
United States Postal Service "Express Mail Post Office to addressee"
Service under 37 C.F.R. Sec. 1.10 addressed to: Box Patent Application
Assistant Commissioner for Patents, Washington, D.C. 20231, on
October 23, 2000.

Express Mailing Label. No.: EK 834 920 035 US


John H. Sherman, Reg. No. 16,909

CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority to U.S. Provisional Application Serial No. 60/074,145, filed February 9, 1998, which is hereby incorporated by reference herein in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a system and method for performing an optical read and a RF read on a carrier unit. More particularly, the present invention relates to a system and method for performing an optical read prior to establishing communication between a RF interrogation device and a RF tag, and more particularly to a system and method for performing a bar code read prior to establishing communication between a RF interrogation device and a RF tag.

2. Description of the Related Art

Given the fast pace of commerce today, it is imperative that the movement of articles of manufacture ("goods") from one location to another be tracked. Goods must be identified quickly, including information concerning the source of the goods, the location of the goods and the destination of the goods. When goods are stacked on pallets in a warehouse, on a loading dock, in a railcar, or in any similar temporary storage environment, it is imperative that the identification of the goods be made quickly and relatively inexpensively so inventory of the goods can be had as the goods are transported further down the commerce stream without undue delay.

The use of passive RF transponder devices is common. These devices require no internal power source and can be manufactured relatively inexpensively in mass quantities. In a

passive tag system, a radio transponder uses radio frequency energy in a RF interrogation device (tag reader) to communicate with a passive RF tag. An energizing signal is transmitted by the RF interrogating device, which creates an energizing field. This field powers up the passive transponder RF tags within the field and enables the RF tags to transmit their identity,
5 and other data, to the interrogating device.

Regarding RF tags, there are several common varieties. RF tags for articles, or goods, are typically passive, deriving all their operational power from a RF interrogation signal. Active tags having a battery or other internal power source are typically used for vehicle, or other large object, tracking and/or identifying. A passive/active RF tag includes a passive receiver section and an active processing, storage and/or transmitting section. One-bit tags are generally used in an electronic article surveillance (EAS) system in retail stores as a security measure to protect against theft. For one-bit tags, the logical state of the security bit is detected by an interrogation device near the store exit. An alarm will sound if the article containing the RF tag passes through an interrogation signal from the interrogation device with an incorrectly 15 coded tag, i.e. a tag for an unpaid article coded as not yet being permitted to leave the store premises.

For passive RF tag operation, frequently a principle called backscatter modulation is used for data communication from the RF tag to the RF interrogating device. The energizing field created by the interrogating device is typically in the form of a carrier wave signal at a fixed 20 frequency. The energy of the transmitted carrier wave signal is received by the coil, or antenna, of the RF tag, is rectified, and is used to power the RF tag. The carrier may be in the form of a

header that is transmitted for a sufficient period of time, e.g. 30 milliseconds, to enable the RF tag to “charge up” prior to communicating with the interrogating device. After the charge up period, the RF tag device is able to transmit control signals, timing signals, data or otherwise communicate with the interrogating device.

5 The RF tag generates a signal for the interrogating device in the form of a data stream, which may include a clock signal and data stored in the RF tag. This generated signal may be in the form of a modified manchester encoded signal at a second frequency (e.g. 10 KHz) that is shifted from the original interrogating signal (e.g. 915 MHz) by the clock rate of the RF tag. The data stored in the RF tag is used within the RF tag to drive a shorting, or shunt, transistor connected across the RF tag antenna. This has the effect of changing the reflectivity of the RF tag antenna with respect to the interrogating signal from the interrogating device and causes some of the received energy from the interrogating device to be reflected back towards a receiver on the interrogating device. The RF tag acts as a field disturbance device by reflecting the incident RF interrogation signal in a coded manner. The energy reflected by the RF tag may take the form of 10 data packets. A simple receiver on the interrogating device, using the RF tag signal as a local oscillator, can decode the received signal from the RF tag and extract the encoded data.

15

Optical scanning devices are used to read a bar code printed on a label which is attached to individual goods or attached to a shipping container, a storage container, a box, a shipping pallet, or to any similar container, herein referred to as a “carrier unit”, for transporting or 20 temporarily storing goods. Optical scanners typically perform a read of one-dimensional coded images (e.g. bar codes) or a read of two-dimensional coded images. The two-dimensional

codes typically include more information than the one-dimensional variety, but two-dimensional readers typically cost more than one-dimensional readers.

Performing an optical read on a bar code has associated problems. The operator of the reader must be in line of sight with the bar code and must be close enough for optimum 5 performance of the reader. A dirty scanning window on the reader, or a dirty or torn bar code label will cause a misread leading to errors. Additionally, information encoded in the bar code cannot be changed without printing another bar code that contains the new information.

Using a RF tag reader also has associated problems. In a large storage facility, such as a warehouse, using a RF tag reader alone to identify and track goods may be difficult and/or inefficient. A RF tag reader sends out an interrogation signal which is responded to by one or more tags which have received the interrogation signal using a chosen preestablished protocol. Unfortunately, the physical location of the carrier unit used to store the goods may be indiscernible.

Neither an optical reader nor a RF reader can, by itself, quickly and accurately ascertain 15 both the physical location of the desired carrier unit or individual goods and identify, and read from and/or write to a RF tag associated with the desired carrier unit or individual goods.

SUMMARY OF THE INVENTION

Using the system and method of the present invention, which includes the combined functionality of an optical bar code reader and a RF tag reader, information in regard to an individual carrier unit, or the individual goods associated therewith, can be ascertained quickly and efficiently. The physical location of the carrier unit or individual goods can also be ascertained. Since a bar code label typically includes only basic information about the carrier unit or goods, such as the identity of the goods, or other limited scope of information, a RF tag may be used in conjunction with a bar code label to supplement the information needed concerning the carrier unit and/or the goods.

RF tags are wireless responsive devices attached to or embedded within articles of commerce or other objects to be communicated with by an interrogation device using RF communication or other wireless communication scheme. Each responsive device contains within its memory or otherwise stored within, a communication sequence, or tag sequence, for a RF tag which is unique to and identifies the individual responsive device. Also contained within each responsive device is data which corresponds to information describing the goods to which it is associated, such as the source of the goods, the goods' destination, price, preferred storage temperature, current temperature, weight, etc.

The responsive device may be interrogated at a point of sale terminal, such as at a store checkout counter, or on a loading dock, in a warehouse, in a truck, etc. Any number of stationary or hand-held devices may be used to transmit an interrogation signal to attempt to communicate

with each of the plurality of responsive devices.

In the present invention, a dual function reader device is used to scan an optical bar code attached to a carrier unit, which includes a storage container, shipping pallet, or other temporary carrier for storing goods in commerce. An optical scanner portion of the dual function reader

5 reads the bar code which provides data to the device and causes an indicator light disposed on the bar code label to illuminate, indicating to the operator of the scanner that the bar code for the desired carrier unit has been read. The bar code includes data corresponding to the identity of the goods stored with the carrier unit, or the identity of the carrier unit itself. A RF tag button disposed on the carrier unit could be pushed by an operator to enable the RF tag

10 associated with the carrier unit to enable the RF tag to communicate with the RF read portion of the reader.

The data read from the bar code label may be the address of a RF tag attached to the goods and/or attached to the carrier unit. An RF tag reader portion of the dual function reader uses the address obtained from the optical read operation to address the individual RF tag

15 associated with the carrier unit. The reader then communicates with the RF tag of the carrier unit to obtain more detailed information regarding the goods, such as the source, the destination, the storage temperature, the current temperature, weight sensing information, bacteria sensing information, shelf-life information, etc. Information about the carrier unit itself is also obtained, regarding the inventory of goods stored with the carrier unit, the source

20 of the carrier unit, the destination of the carrier unit, the last usage of the carrier unit, etc.

A small low-powered radio is attached to the carrier unit, where, in reporting mode, the radio periodically wakes up and transmits status information to a base station or to an access point for a wired or wireless infrastructure network. In status mode, a base station addresses a particular carrier unit's RF tag and then establishes communication with the RF tag to obtain 5 status information regarding the carrier unit and/or the associated goods.

Moreover, other aspects of the present invention will become apparent with further reference to the drawings and specification which follow.

BRIEF DESCRIPTION OF THE DRAWINGS

A better understanding of the present invention can be obtained when the following detailed description of the preferred embodiment is considered in conjunction with the following drawings, in which:

5 Figure 1 schematically illustrates a dual function reader device and a carrier unit in accordance with the present invention;

10 Figure 2 schematically illustrates an optical bar code label in accordance with the present invention;

15 Figures 3-5 illustrate various embodiments of carrier units in accordance with the present invention;

20 Figure 6 illustrates an embodiment of a dual function reader device in accordance with the present invention;

25 Figure 7 schematically illustrates the internal components of the reader device of Fig. 6;

30 Figure 8 is a block diagram of an embodiment of an RF tag in accordance with the present invention;

35 Figure 9 schematically illustrates a carrier unit and a biological sensor in accordance with the present invention;

40 Figure 10 schematically illustrates a stack of carrier units and shipping crates, including a pressure sensor, in accordance with the present invention; and

45 Figure 11 illustrates an embodiment of a grid system for a carrier unit location system in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In commerce today, articles of commerce, or goods, are typically transported from manufacturer to wholesaler to retailer by boat, plane, train or truck in shipping containers, boxes, crates, or truck trailers, and/or stored on shipping pallets or other similar shipping

5 platforms for temporarily holding or storing goods. These containers or pallets are generally described herein as "carrier units". At some point in this commerce stream, the goods are typically stored, at least temporarily, in a depot or warehouse awaiting further transport to their ultimate destination. Inventory control of the numerous carrier units and associated goods in a warehouse setting presents a formidable task. Carrier units being loaded or unloaded from planes, boats, trains, trucks or other shipping vehicle may utilize a passive RF tag system to identify and track the goods in transit. Passive tag systems built in accordance with the present invention may be utilized to detect and identify a particular carrier unit, or good, and the associated price, and other information, for goods in transit, in storage, or being purchased by a consumer in a retail store.

15 Referring to Fig. 1, RF tag 60 associated with a carrier unit 100 responds to a RF interrogation signal generated by a RF interrogating device. The interrogating device is a dual combined function optical read and RF read reader 10, described below, which is illustrated as being a hand-held inventory control device capable of being attached by a tether 24 to a warehouse forklift (not shown) or other large device having its own power source, or may be a
20 portable self-powered reader carried by an individual operator. The interrogating device could otherwise be a stationary device, such as a base station (not shown) located in close proximity

to where the carrier unit 100 is being temporarily stored. A RF response signal generated by the RF tag 60 contains the identity of the carrier unit 100, the goods stored within or on carrier unit 100, the source, destination, price and other data regarding the goods or the carrier unit 100, such as shelf-life or storage temperature information for the goods. A computer (not shown) coupled to the interrogating device may utilize this information to track the carrier unit 100 and/or the goods.

These carrier units 100 also come marked or labeled with an optical bar code label 50, known in the art. These one-dimensional or two-dimensional bar codes typically provide only limited information about the carrier unit 100, such as the identity of the source of the carrier unit 100, or the destination of the carrier unit 100 and/or the goods associated therewith.

To provide additional information about the carrier units 100 and the goods, RF tags 60 are used. A RF tag 60 is affixed to the goods themselves (not shown), is affixed to an outer surface of the carrier unit 100 as shown, or is embedded within the structure of the carrier unit 100 (not shown).

Still referring to Fig. 1, in general, the present invention utilizes the dual function reader 10 to obtain information regarding a particular carrier unit 100, or regarding the goods stored on or within the carrier unit 100. A selected carrier unit 100 is approached by an operator (not shown) holding the reader 10. The operator then points the reader 10 at the optical bar code 50 on the selected carrier unit 100 and pulls the trigger 14 for an optical read operation. The reader 10 performs an optical read of the optical bar code 50. A successful read causes an

indicator light (not shown) associated with the bar code 50 to be illuminated in a blinking pattern, or otherwise. The indicator light is located on the bar code label 50, or is otherwise located on an outer surface of the carrier unit 100 so it is easily observable by the operator. The information obtained by the read operation is displayed on a display window (not shown) on 5 the reader 10.

The operator can then decide to perform a separate RF read operation of any RF tag 60 associated with the carrier unit 100, or with the goods stored in or on the carrier unit 100, based on the information obtained from the optical read operation. If the optical read information reveals that the carrier unit 100 does not contain the type of goods the operator was searching 10 for, then no RF read need be performed and the next carrier unit 100 is selected.

If the optical read operation reveals that the operator has selected the proper carrier unit 100, an RF read operation is performed to obtain additional information about the carrier unit 100 or the goods. The optical read may provide the reader 10 with the specific identification of the carrier unit 100, or the goods, which may include a specific RF tag address for an RF tag 60 15 disposed on, or within, the carrier unit 100, as previously described. The RF read operation initiates a transmission sequence which is transmitted to the RF tag 60 via the reader 10. Other RF tags in the vicinity associated with other carrier units may also receive the RF transmission sequence, but they do not respond to the transmission signal since their respective specific 20 identification code, or address, has not been transmitted. Only the RF tag 60 having the corresponding identification code or address will respond to the RF transmission signal with a responsive data sequence transmission.

An operator, in accordance with the present invention, can write information to the RF tag 60, as well. The RF tag 60 for a carrier unit 100 may need to be updated with a more current inventory of the goods being stored within, or on, the carrier unit 100. Additionally, if the carrier unit 100 destination changes while in transit, this information could also be updated 5 by the operator. In general, any information included within the RF tag 60 could be modified by an operator, unless it was read-only, or otherwise write protected, data.

Figure 2 illustrates schematically a typical optical bar code 50 printed on a label. Various formats for bar codes are known to those in the art. Indicator light 52 is disposed on a portion of, or in close proximity to, bar code 50 label. The function of indicator light 52 in regard to the present invention will be explained below.

Figures 3-5 illustrate various embodiments of carrier units having an optical bar code 50 label attached thereto. Each figure illustrates a RF tag 60 attached to the respective carrier shown. In Fig. 3, the carrier units are drums 55 which are 55 gallon drums storing solid or liquid chemicals, or other agents. Each drum 55 includes a bar code 50 affixed to, or printed 15 on, an outer surface. Information on the bar code 50 is typically limited to the identity of the contents of the drum 55, with possible additional information concerning the source or destination of the drum 55, and/or the toxicity of its contents. Similarly, a bar code 50 label affixed to, or printed on, the crate 57 of Fig. 4, or on the stacked boxes 56 stored on pallet 53 of Fig. 5, contains only limited information, as previously mentioned.

20 Figure 6 illustrates a dual function reader 10 used in accordance with the present

invention. The reader 10 includes a gun-shaped housing 12, a handle 16, a trigger 14, a radio frequency (RF) antenna 20, a data entry device 18, a scanning window 22 and a display window 26. Trigger 14 may be a single trigger or a plurality of triggers - one trigger for each of a plurality of dedicated functions, such as an optical read function or a RF read function.

5 Antenna 20 provides two-way RF communication between reader 10 and a RF tag 60, as discussed elsewhere herein. Scanning window 22 allows the bar code scanner circuit 34 (Fig. 7) disposed within reader 10 to illuminate optical bar codes for receipt of the data by reader 10 for storage, processing and/or displaying by reader 10.

The reader 10 is configurable into one of a plurality of functional modes of operation.

10 In one mode of operation, an operator aims reader 10 at the optical bar code 50 of a carrier unit 100. The operator then squeezes trigger 14 on reader 10 to perform an optical read of bar code 50. The operator must be in line of sight of the desired carrier unit 100. If the data received by the optical read, and displayed on the reader 10, indicates the desired carrier unit 100 has been located, the operator then squeezes trigger 14 to perform a RF read of RF tag 60 of carrier unit 15 100.

20 In another mode of operation, the operator first squeezes trigger 14 to perform a RF read operation on RF tag 60 of a carrier unit 100. The operator need not be in line of sight of the carrier unit 100. If the RF read operation is successful, and the operator needs to read additional information from the optical code 50, the desired carrier unit 100 is physically located and trigger 14 is squeezed to perform an optical read operation.

In an additional mode of operation, the operator squeezes trigger 14 after locating the desired carrier unit 100 to perform a simultaneous RF read operation and optical read operation on RF tag 60 and optical bar code 50, respectively.

In a still further mode of operation, suited for situations where there are numerous carrier units 100 in close proximity to one another, an operator aims reader 10 at a desired carrier unit 100 and squeezes trigger 14 to first perform an optical read to determine whether the carrier unit being aimed at is the desired carrier unit. Data is obtained from the carrier unit regarding its identification information, contents, destination, etc. Once the reader 10 obtains the identification information from the optical read operation, reader 10 automatically performs a RF communication sequence with the RF tag 60 associated with that desired carrier unit 100. The identification of the RF tag of that desired carrier unit 100 is used during the RF communication sequence to communicate only with the RF tag 60 of the desired carrier unit 100. A RF write operation may also be performed to write data to RF tag 60 via reader 10.

Reader 10 includes a battery pack 38 (Fig. 7) which includes a single battery or a plurality of batteries. The batteries are rechargeable. An optional tether 24 (Fig. 6) connects reader 10 to an external power source (not shown). In a warehouse setting, the tether 24 connects the reader 10 to a power outlet on a forklift or other vehicle, or to a power outlet installed within the warehouse infrastructure. The power outlet may be for an ac or a dc voltage source. The battery pack 38 of the illustrated reader 10 is a dc power source which can be recharged by connecting the tether 24 to an external power source, as described. The data entry device 18 may be a keypad, a liquid crystal display (LCD) touch screen, or other similar

data entry device used to manually input data to reader 10. Display window 26 is a light emitting diode (LED) display, a LCD device, a cathode ray tube (CRT) display, or other similar device known in the art for displaying information on a hand-held low power, battery operated device.

5 Referring to Fig. 7, a block diagram schematic of an embodiment of the internal components of reader 10 is illustrated. Antenna 20 is coupled to RF transceiver 32, which is in turn coupled to processing circuit 36. Optical bar code scanner circuit 34, which is also coupled to processing circuit 36, transmits and receives light signals 42 via scanning window 22 (Fig. 6) of reader 10. Various implementations of optical bar code scanner circuits are known in the art. The data received from the optical read operation of the bar code 50 is provided to the processing circuit 36 by the scanner circuit 34. Processing circuit 36 then forms a transmission signal to be transmitted, via RF transceiver 32, to a RF tag 60 associated with the carrier unit 100 that was optically read. The transmission signal will be specifically addressed to the associated RF tag for the carrier unit based on the address or code obtained
10 during the optical read operation.

If an optical read operation of a bar code is successful, scanner circuit 34 generates a data read signal that is provided to processing circuit 36 to indicate a successful optical read. In another embodiment, processing circuit 36 may itself generate the data read signal for a successful optical read operation of a bar code. In one embodiment, the data read signal is used
20 by processing circuit 36 to generate an enable signal which is provided to RF transceiver 32. This enable signal enables transceiver 32 to perform a RF read operation, upon completion of a

successful optical read operation. Processing circuit 36 also includes a manual selection function, selected by an input on data entry device 18 (Fig. 6), which allows either an optical read operation by enabling scanner circuit 34, or allows a RF read operation by enabling RF transceiver 32. It is desirable to limit the use of RF transceiver 32 while reader 10 is powered by battery pack 38 to extend the life of the battery pack 38.

5

Battery pack 38 supplies power to all the components of reader 10, as illustrated. An external power connection 40 couples to tether 24 (Fig. 6) and supplies power to power regulator circuit 44, shown as part of battery pack 38. Power regulator circuit 44 provides ac to dc conversion functions, current limiting functions, and other functions necessary and known to those in the art for supplying the circuitry of reader 10 with external power from an ac or a dc source. Power regulator circuit 44 may otherwise be formed as a portion of processing circuit 36, or may be a standalone circuit within reader 10.

10
15
20

15

20

An automatic backup circuit 46, illustrated as part of processing circuit 36, is utilized to automatically enable RF transceiver 32 if a data read signal is not generated a predetermined period of time after scanner circuit 34 first attempts to read an optical bar code for a selected carrier unit 100. The backup circuit 46 may be configured such that after a certain number of attempts to read a bar code, it would automatically enable RF transceiver 32 and send a message to the display 26 (Fig. 6) of reader 10 that the optical read was unsuccessful and that RF read operation is now enabled. Otherwise, a timeout period could be assigned to an optical scan operation, after which if an optical read is unsuccessful, the RF transceiver 32 could be enabled by automatic backup circuit 46. Automatic backup circuit 46 is disabled while reader

10 is not drawing power from an external power source via external connection 40.

Referring to Fig. 8, a RF tag 60 is illustrated, including an antenna 20, which may be a coil, demodulating circuit 66 and a tag processing circuit 64. Modulating circuit 62 may be as simple a circuit as a transistor coupled to the antenna 20 and connected to ground, such that as 5 the tag transmission sequence is received from processing circuit 64 to be transmitted to reader 10, the logical ones and zeros comprising the tag sequence will cause the transistor to short, or shunt, the antenna 20 to ground when a logical one is received, in one embodiment, or when a logical zero is received, in an alternative embodiment. Processing circuit 64 includes a memory element 68 which stores a tag sequence and other data for RF tag 60. Various other modulating circuits of varying degrees of complexity are well known in the art.

100 99 98 97 96 95 94 93 92 91 90 89 88 87 86 85 84 83 82 81 80 79 78 77 76 75 74 73 72 71 70 69 68 67 66 65 64 63 62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

In the operation of RF tag 60, a transmission from reader 10 is received by RF tag 60 via antenna 20 and is provided to demodulation circuit 66 where the signal is demodulated using known methods. The demodulated received signal is then provided to processing circuit 64, which includes storage element 68 which includes data about the carrier unit 100 or the 15 goods stored within or on the carrier unit 100, such as the source, destination, price, preferred storage temperature, current temperature, stress/pressure, biological process analysis, etc. Processing circuit 64 includes logic which determines whether the demodulated received signal is addressing the RF tag 60. If so, a data sequence from storage element 68 is provided to modulating circuit 62 for transmission via antenna 20 to the interrogating reader 10 as a data 20 sequence transmission signal. If RF tag 60 is not being addressing by the reader 10, the demodulated signal will not match the specific address code stored in processing circuit 64 and

no responsive data sequence signal will be transmitted by the RF tag 60.

RF tag 60 emits a response to the transmission signal from reader 10 using backscatter modulation to communicate data. An energizing field emitting with the transmission from reader 10 is, in one embodiment, in the form of a carrier wave signal at a fixed frequency. This transmitted energy is received by the coil, or antenna 20, of the RF tag 60, is rectified or otherwise processed by demodulating circuit 66, and is used to power the RF tag 60, which is typically a passive RF tag having no internal power source. RF tag 60 decodes its address in processing circuit 64, matches it against the address, or code, stored in storage element 68, and sends a response if the proper code or address is received and decoded. The response is a modulated RF signal at a frequency different than that of the transmission signal from reader 10. The response signal is typically in the form of a data stream which may include a clock signal and various data regarding the carrier unit, the goods, or both. This generated data sequence may be in the form of a modified manchester encoded signal at a frequency that is shifted from the original transmission signal. The data sequence from RF tag 60 is used to drive a shorting, or shunt, transistor (not shown) connected across the antenna 20. This has the effect of changing the reflectivity of the RF tag antenna 20 and causes some of the received energy from the reader 10, and a clock signal, to be reflected back towards reader 10. The RF tag 60 acts as a field disturbance device by reflecting the incident RF transmission signal from reader 10 in a coded manner. This reflected energy may take the form of data packets.

A simple receiver circuit (not shown) on the RF transceiver 32 (Fig. 7) of reader 10 uses, in one embodiment, the received RF tag 60 clock signal as a local oscillator to decode the

received data signal from RF tag 60 to extract the modified manchester encoded data. In other embodiments, the tag sequence is used to directly modulate the signal from RF tag 60 and no clock is transmitted by the RF tag 60.

Information regarding the status of a biological process for goods within the carrier unit
5 is provided by a biological sensor microchip that senses chemical and biological substances in
real time. Such a sensor has been developed by Texas Instruments, and is schematically
depicted as biological microchip sensor 102 attached to a carrier unit 100 of Fig. 9. The level
10 of E-coli bacteria, for example, could be tracked by the sensor which would provide, in real-
time, that information to the RF tag. A RF read of the RF tag by an operator would provide the
bacterial information to the reader. The operator could then determine whether the bacteria
15 level is above a safe level.

Referring to Fig. 10, information regarding stress/pressure on a carrier unit 100 could be
obtained from information regarding pressure and wall shear stress being applied to one or a
plurality of carrier units 100. For example, when a carrier unit 100, particularly a shipping
15 pallet containing a shipping crate 108, is stacked, great pressure and stress is exerted on the
bottommost carrier unit and shipping crate 108, which may cause either to fail and break or be
crushed. Excessive pressure on the carrier unit 100 would cause damage to the goods within
the carrier unit 100 as well, costing time and money to replace the damaged goods and have
them reshipped. A micro transducer and/or micromachined pressure microsensor 104 is
20 embedded on or within one or a plurality of carrier units 100. Various configurations of micro
transducers and micromachined pressure microsensors are known in the art. Information

regarding excessive pressure is read directly from the pressure sensor 104, or is provided to the RF tag 60 on the carrier unit 100. An operator is alerted of the potential failure. In another embodiment, the RF tag 60 or pressure microsensor 104 has a power source 106 which allows microsensor 104 to broadcast the warning, giving the carrier unit identification, to a local base station, described below with regard to Fig. 11. A central computer (not shown) coupled to the base station could then store the warning and/or send an alert message to a system operator.

Referring to Fig. 11, an embodiment of a grid system for a carrier unit location system in accordance with the present invention is illustrated. A warehouse, or other large storage area, may be sectioned into cells. Figure 11 shows a warehouse building divided into six cells. Many carrier units are typically contained in each cell. If an operator wanted to move a particular carrier unit from the warehouse to load onto a truck, for example, the operator needs to be able to quickly find the carrier unit. Upon arrival at the warehouse, the cell storage location for the carrier unit is recorded, but the exact location within the cell is not. Since each cell may be relatively large, it is important for the operator to be able to quickly ascertain the location of the carrier unit after arriving at the cell of the carrier unit. Each cell may include a base station 75 which can be programmed to send a transmission signal addressed, or otherwise coded, for the specific carrier unit being located. The operator may also initiate the delivery of information regarding the identification of the carrier unit into the base station 75, via keyboard entry directly at the base station 75, or via wireless transmission to the base station 75 from a remote wireless data input device (not shown). A main computer (not shown) coupled to each base station 75 via wired or wireless communication sends the appropriate base station 75 the

carrier unit identification information for the that cell.

Regardless of the method used, a base station 75 transmits the transmission signal for the carrier unit, which upon receipt by a RF tag attached to the carrier unit causes an indicator light 52 on the carrier unit to illuminate. The indicator light 52 may be disposed on bar code 50, as shown in Fig. 2, or may otherwise be located in close proximity to the bar code 50. In either embodiment, a small power source 54 and a light sensor 51 are coupled to the indicator light 52. When the light from scanner window 22 of reader 10 is detected by light sensor 51 tuned to detect light of a predetermined frequency, it causes the indicator light 52 to turn on and illuminate. Various implementations of circuitry to perform this function are known in the art. Additionally, the use of small, low powered batteries are known in the art. The illumination may be steady or any on/off or blinking pattern. The indicator light 52 may or may not be located on the optical bar code label, as discussed above. By illuminating the indicator light 52, the specific carrier unit with a given cell is quickly and easily identified. The carrier unit can then be optically read and/or RF read as described above, or simple moved out onto a truck or other transport medium.

In another embodiment, a RF tag enable button 63 (Fig. 2) is attached to the carrier unit. Button 63 may be in close proximity to bar code 50 label for ease of operation. An operator approaches a carrier unit 100 to be read by reader 10, pushes button 63 and reads information from the RF tag 60. Pushing button 63 enables the RF tag 60 to be read by reader 10. Otherwise, without button 63 being pushed, the RF tag 60 does not respond to reader 10.

A small low-powered radio 59 (Figs. 4 and 5) is attached to the carrier units 57 and 53, respectively, where the radio 59 is configurable to two modes. One mode is a query mode, the other mode is a report mode. In query mode, a base station 75 (Fig. 11) sends an interrogation signal, including identification information, to a specific RF tag 60. The RF tag 60 decodes its own identification code and then transmits its data to the base station. In report mode, radio 59 periodically wakes up and transmits status information to a base station 75 (Fig. 11) or to an access point for a wired or wireless infrastructure network.

In another embodiment, once inside a desired cell (1-6) in the warehouse, the operator inputs the identification number for the carrier unit to be located and the reader 10 then transmits the signal addressed for the particular carrier unit. This step is accomplished prior to the RF read, discussed above. Upon receipt of the transmission signal by an RF tag associated with the carrier unit, indicator light 52 of the desired carrier unit will illuminate, as previously described.

In summary, the present invention includes a system and method which utilizes a dual
15 function reader, which may be a hand-held inventory control device, which first performs an
optical read of an optical bar code on a carrier unit, then based on the identification or other
information obtained from the optical read a RF read is made of a RF tag attached to, or within,
the carrier unit. An indicator light on the carrier unit illuminates when the optical read is
completed, which allows an operator to visually verify that the optical read has transpired for the
20 desired carrier unit. The RF tag provides data regarding the inventory of the goods stored within,
or on, the carrier unit, the temperature of the goods, the shelf-life of the goods, the source and/or

destination of the carrier unit and/or the goods, and other pertinent information. Data can also be written to the RF tag by the reader.

Although a system and method according to the present invention has been described in connection with the preferred embodiment, it is not intended to be limited to the specific form set forth herein, but on the contrary, it is intended to cover such alternatives, modifications, and equivalents, as can be reasonably included within the spirit and scope of the invention as defined by the appended claims.

CLAIMS

1 1. A dual function reader device, comprising:

2 a housing, including a handle disposed at one end of said housing and including at one

3 trigger disposed along said handle;

4 a radio frequency (RF) antenna disposed along said housing;

5 an optical bar code scanner circuit disposed within said housing;

6 a RF transceiver disposed within said housing; and

7 a processing circuit coupled to said antenna, to said RF transceiver and to said scanner
8 circuit;

9 wherein a data read signal is generated by said reader after a successful optical read
10 operation is completed; and

11 wherein said processing circuit forms a RF transmission signal after receiving said data
12 read signal.

1 2. The device of claim 1, further including a tether attached to said device housing.

1 3. The device of claim 1, further comprising a battery pack disposed within said

2 housing, said battery pack being electrically coupled to said processing circuit and to said
3 transceiver.

1 4. The device of claim 1, further comprising a data entry device disposed on said

2 device housing, said data entry device being coupled to said processing circuit.

1 5. The device of claim 1, wherein said transceiver is enabled to transmit said
2 transmission signal after said data read signal is received by said RF transceiver.

1 6. The device of claim 1, further comprising an automatic backup circuit which
2 automatically enables said transceiver if no data read signal is generated a predetermined period
3 of time after said scanner circuit attempts to read an optical bar code.

1 7. The device of claim 1, wherein said processing circuit includes a manual
2 selection function which causes either said transceiver or said scanner circuit to be enabled.

1 8. The device of claim 6, wherein said automatic backup circuit is disabled if said
2 device is not coupled to an external power source.

1 9. The device of claim 1, wherein said data read signal is generated by said scanner
2 circuit after said scanner circuit receives uncorrupted data from an optical bar code.

1 10. A location indicating bar code label, comprising:
2 a bar code label which includes a bar code pattern printed on said label;
3 an indicator light disposed on said bar code label; and
4 a power source coupled to said indicator light;
5 wherein said power source is coupled to said indicator light.

1 11. The label of claim 10, further comprising a light sensor coupled to said indicator
2 light.

1 12. The label of claim 10, wherein said indicator light is illuminated when said bar
2 code label is scanned by a light source having a predetermined frequency.

1 13. A radio frequency (RF) responsive device for temporarily storing articles of
2 commerce, comprising:

3 a carrier unit;
4 a RF transponder device disposed on said carrier unit; wherein
5 an optical bar code disposed on said carrier unit;
6 said transponder device includes a data sequence regarding goods stored by said carrier
7 unit.

1 14. The device of claim 13, further comprising a low-powered radio disposed on
2 said carrier unit.

1 15. The device of claim 14, wherein said radio periodically wakes up and transmits a
2 status message.

1 16. The device of claim 13, wherein said transponder data sequence includes at least

2 one data set selected from the following group of data sets: the source of said carrier unit, the
3 destination of said carrier unit, the source of the goods stored by the carrier unit, the destination
4 of goods stored by said carrier unit, an inventory of goods stored by said carrier unit, the shelf-
5 life of goods stored by said carrier unit, the current temperature of goods stored by said carrier
6 unit, a preferred storage temperature for goods stored by said carrier unit, biological sensor data
7 for goods stored by said carrier unit, and pressure sensor data for said carrier unit.

17. The device of claim 13, wherein said carrier unit comprises a railroad car.
18. The device of claim 13, wherein said carrier unit comprises a shipping container.
19. The device of claim 13, wherein said carrier unit comprises a shipping pallet.
20. The device of claim 13, wherein said carrier unit comprises a truck trailer.
21. A dual mode article identification system for goods stored by a carrier unit, comprising:
 - a dual mode reader device;
 - a temporary carrier unit for storing articles of commerce;
 - an optical bar code disposed on said temporary carrier unit;
 - a radio frequency (RF) transponder device disposed on said temporary carrier unit; and
 - a plurality of goods stored by said temporary carrier unit;

8 wherein said reader device reads said optical bar code and communicates with said RF
9 transponder device.

1 22. The system of claim 21, wherein said reader device includes an optical scanner
2 portion and a RF transceiver portion.

1 23. The system of claim 21, further comprising an indicator light disposed on said
2 carrier unit in close proximity to said optical bar code.

1 24. The system of claim 21, further comprising a biological sensor device for
2 sensing biological activity for said goods.

1 25. The system of claim 21, further comprising a pressure sensor for sensing
2 pressure exerted on said carrier unit.

1 26. The system of claim 21, further comprising a sensor for providing status data to
2 said RF transponder device.

1 27. A method of communicating between a reader device and a carrier unit, wherein
2 said carrier unit includes a plurality of goods stored therewith, includes an optical bar code
3 disposed thereon, and includes a radio frequency RF transponder device disposed thereon, and
4 wherein said reader device includes an optical bar code scanner and a RF transceiver, said

5 method comprising the steps of:
6 optically scanning said optical bar code using said reader device;
7 establishing RF communication between said reader device and said RF transponder
8 device; and
9 delivering status information from said carrier unit to said reader device.

1 28. The method of claim 27, wherein said status information comprises status
2 information for said plurality of goods.

1 29. The method of claim 27, further comprising the step of transmitting status
2 information from said reader unit to said carrier unit.

1 30. The method of claim 27, wherein said status information comprises status
2 information for said carrier unit.

1 31. The method of claim 27, further comprising the step of transmitting at least one
2 location detection signal for geographically locating said carrier unit.

1 32. The method of claim 27, further comprising the step of communicating with said
2 RF transponder via a base station.

ABSTRACT OF THE DISCLOSURE

A system and method is described which utilizes a dual function reader device, which may be a hand-held inventory control device, which first performs an optical read of an optical bar code on a carrier unit, then based on the identification or other information obtained from the optical read a RF read is made of a RF tag attached to, or within, the carrier unit. An indicator light on the carrier unit illuminates when the optical read is completed, which allows an operator to visually verify that the optical read has transpired for the desired carrier unit. The RF tag provides data regarding the inventory of the goods stored within, or on, the carrier unit, the temperature of the goods, the shelf-life of the goods, the source and/or destination of the carrier unit and/or the goods, or other information. Data can also be written to the RF tag by the reader.




FIG. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




FIG. 6




Fig. 7




Fig.8




Fig. 9





Fig. 10

FIG. 11



**DECLARATION FOR PATENT APPLICATION
AND POWER OF ATTORNEY**

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first, and sole inventor (if only one name is listed below) or an original, first, and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **COMBINED OPTICAL AND RADIO FREQUENCY TAG READER**, the specification of which

(check one) is attached hereto
 was filed on _____
 as Application Serial No. _____
 and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim the benefit under Title 35, United States Code, §§ 119(e) and 120, of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

Ser. No. 60/074,145 02/09/98 PROVISIONAL
 (Provisional Application) (Filing Date) (Status)

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

H. Shannon Tyson, Jr.	Reg. No. 42,193
James D. Bennett,	Reg. No. 37,550
Michael R. Cannatti,	Reg. No. 34,791
James B. Gambrell,	Reg. No. 17,920
Mark J. Gatschet	Reg. No. 42,569
Dennis W. Gilstad,	Reg. No. 36,810
Gary W. Hamilton,	Reg. No. 31,834

Mira L. Helms	Reg. No. 43,668
H. Dale Langley,	Reg. No. 35,927
Gloria L. Norberg,	Reg. No. 36,706
Russell C. Scott,	Reg. No. 43,103
Adam D. Sheehan,	Reg. No. 42,146
Richard J. Smith,	Reg. No. 30,496
Pete A. Smits	Reg. No. 39,036
Gary R. Stanford,	Reg. No. 35,689

Of: Akin, Gump Strauss, Hauer & Feld, L.L.P.
 816 Congress Avenue, Suite 1900
 Austin, TX 78701
 (512) 499-6219; and

I also hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

John H. Sherman	Reg. No. 16,909
Donald R. Schoonover	Reg. No. 34,924
Winfred O.E. Schellin	Reg. No. 25,916
(Of Cedar Rapids, Iowa)	
Sean Patrick Suiter (Of Omaha, NE)	Reg. No. 34,260
H. Robert Henderson (Of Des Moines, IA)	Reg. No. 18,486
Michael O. Sturm (Of Des Moines, IA)	Reg. No. 26,078
John E. Cepican (Of Davenport, IA)	Reg. No. 26,851
Richard L. Fix (Of Des Moines, IA)	Reg. No. 28,297
William H. Wright (Of Washington, D.C.)	Reg. No. 26,424
Harold M. Knoth (Of Davenport, IA)	Reg. No. 14,469

Address all telephone calls to H. Shannon Tyson, Jr. at telephone no. (512) 499-6200
 Address all correspondence to H. Shannon Tyson, Jr.
Akin, Gump, Strauss, Hauer & Feld, L.L.P.
816 Congress Avenue
1900 Frost Bank Building
Austin, Texas 78701

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

First named inventor:

Full name James D. Bennett Inventor's Signature JDB Date 2/9/99
Residence Austin, Texas Citizenship United States
Post Office Address 11712 Shoshone Drive, Austin, Texas 78759